

8400 Green Meadows Dr. P.O. Box 545 Lewis Center, OH 43035

P: 740.548.4100 F: 740.548.7616

## THIS PRODUCT DOES NOT REQUIRE AN MSDS PER OSHA DEFINITION

## **PRODUCT IDENTIFICATION:**

## FLEXIBLE SUPERABRASIVE TOOLING - RESIN

FLEXIBLE SUPERABRASIVE TOOLING - RESIN IS CLASSIFIED AS AN "ARTICLE" BY THE HAZARD COMMUNICATION STANDARD AND ARE THEREBY EXEMPT FROM THE MSDS STANDARD AS IT MEETS ALL 3 CRITERIA LISTED BELOW.

PER OSHA REGULATION 29CFR 1910.1200(c)

"ARTICLE" MEANS A MANUFACTURED ITEM OTHER THAN A FLUID OR PARTICLE:

- (i) WHICH IS FORMED TO A SPECIFIC SHAPE OR DESIGN DURING MANUFACTURE;
- (ii) WHICH HAS AN END USE FUNCTION(S) DEPENDENT IN WHOLE OR IN PART UPON ITS SHAPE OR DESIGN DURING END USE; AND
- (iii) WHICH UNDER NORMAL CONDITIONS OF USE DOES NOT RELEASE MORE THAN VERY SMALL QUANTITIES, E.G., MINUTE OR TRACE AMOUNTS OF HAZARDOUS CHEMICAL (AS DETERMINED UNDER PARAGRAPH (d) OF THIS SECTION), AND DOES NOT POSE A PHYSICAL HAZARD OR HEALTH RISK TO EMPLOYEES.

CREATED: REVIEWED AND REVISED:

BY: D. ANDERSON BY: D. ANDERSON

DATE: 04/01/2011 DATE: 07/12/2011 - FORMAT CHANGE

01/25/2013 - REVIEWED